

DIMENSIONI WINCH.DWG

Corso Sforza, 110 - 48010 Cotignola (Ra) Italy
email: engineering@aa-parts.com
© 2011 - AA-Parts - All right reserved

[illegible]

Always use the mounting head cap screws M3x6 (M3x0.23 inch) with washer and check that they do not interfere with the gears of the winch.

<i>Screw type</i>	Deck thickness
Head cap screw M3x6 with washer	from 0,2 to 2,3 mm

VIEW FROM ABOVE
DRUM OMITTED

X Series - 49
R Series - 55
X Series - 1.92
R Series - 2.16

Drum Ø 32 - 20
Drum Ø 42 - 25

Drum Ø 32 - 0.78
Drum Ø 42 - 0.98

$$\frac{\text{Min thickness} - 0,2}{0.007}$$

X Series - 65
R Series - 75
X Series - 2.55
R Series - 2.95

X Series 51
R Series 54
X Series 2.00
R Series 2.12

$$\frac{cX - cR - 1.77}{pR - 1.81}$$

VIEW FROM ABOVE

Double System Drum™ Ø 32 mm - 40
Double System Drum™ Ø 42 mm - 50
Double System Drum™ Ø 32 mm - 1.57
Double System Drum™ Ø 42 mm - 1.96

$$\begin{array}{r} cX - cR - 32 \\ pR - 33 \\ \hline cX - cR - 1.77 \\ pR - 1.81 \end{array}$$

HULL MOUNTING

Hull thickness - $0,5 \div 0,7$
 $0.019 \div 0$

SIDE VIEW

data shown are not binding and may change without notice

Easy Winch